



Used Cooking Oil Collection - Risk Assessment

No	Risk	Result	Mitigation	Notes
1	Tripping	Fall, risk of injury	Correct footwear/PPE; Ensure work area clear of obstructions	
2	Fall from height	Fall , risk of injury	Avoid working at height without separate Risk Assessment and Method Statement	Working at height includes ANY working at ANY distance above surround
3	Vehicles - movement	Unintended movement	Ensure collection vehicle is correctly parked with parking brake fully applied	Efficacy of brakes to be checked periodically
4	Vehicles - other vehicles	Other vehicles encroach on operations	Collection vehicle and uplift area barriered off to prevent interference	Use suitable chain and supports
5	Vehicles - movement	Injury to other users of site and site staff	On-site movement at no more than walking pace	Observe any local restrictions
6	Spillage	Loss of oil	Follow Method Statement to minimise spillage risk	See MSCAv1.0
7	Spillage	Loss of oil to drain/risk of slipping and falls	Use spill kit to collect and absorb any spill, whether caused by operations or by users or others	Ensure appropriate spill kit always available and replenished as necessary
8	Spillage	Risk of harm to operator	Full use of designated correct PPE	See MSCAv1.0

Health and Safety

- a) On arrival, all persons report to the Recycling Advisor to receive instructions.
- b) All persons to wear Hi – Vis clothing and safety footwear whilst on site.
- c) Persons are not permitted to climb on or into Bins.
- d) Vehicles with amber flashing beacons are to activate the beacons whilst on site.
- e) Drivers must not manoeuvre vehicles on the site until the Recycling Advisor has confirmed that it is safe to do so. The Recycling Centre may need to be closed before the vehicle is given permission to manoeuvre.
- f) Vehicles must only manoeuvre at crawling speed.
- g) All persons are to provide appropriate records and information of the load to assist the Recycling Advisor to complete the necessary documentation.
- h) Where lorry cranes are used, or there are other lifting operations, safety helmets must be worn.
- i) Where drivers need assistance from the Recycling Advisor for reversing, the driver is responsible for ensuring that they maintain sight of the Recycling Advisor and understand the instructions given.
- j) The strainer which is situated under the main lid on the tank must be cleaned on a daily basis or checked regularly for blockages. Appropriate PPE must always be worn when carrying out this procedure.

Rob Murphy
Operations Director

Reviewed 4th October 2012